

# Super Products® **SUPERSUCKER®** INDUSTRIAL VACUUM LOADER



## **LEAVE THE JOBSITE SPOTLESS**

- High power airflow sucks up solids, liquids, sludges and slurries
- Full power extendable boom with back of cab storage
- Full opening, 6 latch tailgate with multi-position safety prop

800.837.9711 • [WWW.SUPERPRODUCTS.COM](http://WWW.SUPERPRODUCTS.COM)

# SUPERSUCKER®



## SPECIFICATIONS

### GENERAL DIMENSIONS

- Length: 33' 7" (approx.)
- Height: 12' 8" (approx.)

### VACUUM SYSTEM

- 8" positive displacement vacuum system
- Vacuum blower, 5800 cfm/28" hg
- Heavy duty transfer case

### FILTRATION SYSTEM

- Single mode filtration enables loading of wet or dry material with no changeover required
- Reverse air pulsation system continuously cleans the 60 snap-ring type, acrylic-coated filter bags
- Easy filter access on top of unit for filter bag change out; bag removal through top covers, side doors for bin cleanout
- One (1) large cyclone with large passage ways for greater airflow, greater performance and greater fuel economy

### DEBRIS BODY

- 18 cu yd debris capacity
- Industrial powder coat finish
- ¼" steel construction throughout entire body and filter chambers
- Body dumping is achieved by one heavy duty, telescopic double-acting cylinder that provides a 51° dump angle.
- The body, bag houses and separator chamber hydraulically raise together, allowing for quick unloading of material
- Full opening tailgate with two lift cylinders
- The hydraulic tailgate latching system is liquid tight and prevents leakage in case of hydraulic malfunction; latches are fully adjustable

### FEATURE OPTIONS

- *Air Excavation Package*
- *5' Extendable Boom with 10' - 15' reach (Height of unit changes to 13' 2")*
- *Rear LED Work Lights*
- *Sludge Pump (Length of unit changes to 35' 2")*
- *Stainless Steel Components*
- *Stainless Steel Debris Body*

### MODEL OPTIONS

- *High Dump*
- *Arctic, designed for extreme temperatures*

\* Disclaimer: Product photos may include standard and/or optional features

 **Super Products®**

